



**Eastto**  
Consistent Quality  
High Performance

**Eastern Petroleum Private Limited**

an ISO 9001-2008 certified company



**Eastto**  
*Shuttering Oil*

## Eastto Shuttering Oil

### INTRODUCTION:

**Eastto** Shuttering Oil is an oil based concrete mold releasing oil, blended from specially selected base oils and excellent additive package for molds in concrete construction works. It offers outstanding de-moulding performances with good surface finish to the molded products. It is non – toxic and does not create misting during spraying or by other applications.

**APPLICATION:** Eastto Shuttering oil is recommended for all types of normal and complex concrete molds including railway sleepers, all types of slab casting, beam, columns, staircase foundations, wall, pipes, poles etc.

### TYPICAL PROPERTIES:

Characteristics	Eastto Shuttering Oil.	Unit
Description	Premium quality general purpose concrete release oil incorporating special oiliness additive. Can be used by brush, swab, spray or dipping.	
Colour	Pale Yellow	
Appearance	Bright & Clear	
Viscosity at 40 Degree C	7.25	cSt
Density at 29.5	.835	Gram/cc

**PACKING:** 210 Litres Drums / 20 Ltr

**COVERAGE:** A Coverage of 30 - 60 sq mtr Ltr by spray is possible depending upon the surface texture. steel or plastic form work will give best result with maximum coverage. Timber form work, coverage will be lesser. Highly Suitable for “MIVAN” Technology.

**SHELF LIFE :** 1 year When stored in original & unopened container under covered space.

**PRECAUTIONS /LIMITATIONS :** To be used in well ventilated condition, since oil is flammable



### Eastern Petroleum Private Limited

#### Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.  
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990  
Email: office@easternpetroleum.in, office@eastto.in,  
Web: www.easternpetroleum.in, www.eastto.in

